

BC40 FRAME / HARDWARE SPECIFICATIONS

FORK MODEL	120MM 44 OFFSET, 100MM 44 OFFSET
STEERER LENGTH	-
FORK AXLE TO CROWN	531MM (120MM) / 506MM (100MM)
FORK RAKE	44MM
BB STANDARD	73MM ENG THREADED
MAX CHAINRING (1X)	36T
FRONT BRAKE	-
REAR BRAKE	POST MOUNT 160
REAR CALIPER BOLTS	-
SEATPOST SIZE	31.6 or 30.9 w/Shim
SEATPOST BINDER	34.9
BINDER TORQUE	5NM
TIRE CLEARANCE FRONT*	29X2.4
TIRE CLEARANCE REAR*	29X2.4
HEADSET TOP	41mm 45x45
HEADSET BOTTOM	52mm 36x45
STOCK HS	Chris King Dropset 3
FRAME SPACING FRONT/REAR	-/12X148
FRONT AXLE LENGTH	-
REAR AXLE LENGTH	12X174
THREAD PITCH	1.5
AXLE TORQUE	12NM
REAR DER HANGER	SRAM UDH
UPPER SHOCK BOLT TORQUE (17)	7NM
LINK SHOCK BOLT TORQUE (11)	7NM
LINK-FT BOLT (9)	7NM
LINK-SW BOLT (13)	11NM
MAIN PIVOT BOLT/SW-FT BOLT (5)	11NM
SHOCK LENGTH/STROKE	190X45MM (120MM) / 190X37.5 (100MM)
SHOCK SPACER FRONT (SHAFT)	8X25MM
SHOCK SPACER REAR (BODY)	8X30MM
REBOUND/COMPRESSION TUNE	M/M
VOLUME TOKEN	1
MAIN PIVOT BEARING DS	63802 OD24 ID15 T7
MAIN PIVOT BEARING NDS	61802 OD24 ID15 T5
REAR LINK BEARING (X2)	63800 OD19 ID10 T5
FRONT LINK BEARING (X2)	63802 OD21 ID12 T5

**MAX TIRE CLEARANCE BASED ON ACTUAL WIDTH W/4MM CLEARANCE ON ALL*